

BREAK IN OIL, BR30 12 X 1QT\CS



JOE GIBBS RACING
MSDS
PO Box 2607
HUNTERSVILLE NC 28078

**Subject: Material Safety Data
Sheets (320)**

Date: 12/08/2010

Dear Sirs and Madams,

Please find enclosed the MSDS's sent to you in accordance to the regulations of the sending country relative to the products(s).

BREAK IN OIL, BR30 12 X 1QT\CS

This information is provided to you for the following reason:

The MSDS has been revised since the product was last ordered by your company.

Thanking you in advance for your cooperation, please accept our best regards,

THE LUBRIZOL CORPORATION
29400 LAKELAND BOULEVARD
WICKLIFFE, OH 44092-2298
PHONE: (440)943-1200
0001 0001292822

Log on to www.mylubrizol.com to get the most up to date MSDS. You can also view the MSDS Change Report online that lists MSDS with changes in the last 30 days.



Prepared according to 29CFR 1910.1200.

1	Chemical Product and Company Identification
----------	--

THE LUBRIZOL CORPORATION
29400 LAKELAND BOULEVARD
WICKLIFFE, OH 44092-2298
PHONE: (440)943-1200

Product Trade Name	BREAK IN OIL, BR30 12 X 1QT\CS
CAS Number	Not applicable for mixtures.
Synonyms	None.
Generic Chemical Name	Mixture.
Product Type	Multipurpose.
Preparation/Revision Date	02 December 2010
Transportation Emergency Phone No.	FOR TRANSPORT EMERGENCY call CHEMTREC: (+1) 703-527-3887 (outside the U.S.), 1-800-424-9300 (in the U.S.)
MSDS No.	1535618-2403972-0121031-102103

2	Hazards Identification
----------	-------------------------------

Appearance	Amber liquid.
Odor	Mild
Principal Hazards	<ul style="list-style-type: none"> This material has no known health hazards.

See Section 11 for complete health hazard information.

3	Composition/Information on Ingredients
----------	---

Hazardous Ingredients	This material has no known hazards under applicable laws.
------------------------------	---

4	First Aid Measures
----------	---------------------------

Eyes	Flush with water at least 30 minutes. Get medical attention if eye irritation develops or persists.
Skin	Wash with soap and water. Get medical attention if irritation develops. Launder contaminated clothing before reuse.
Inhalation	Remove exposed person to fresh air if adverse effects are observed.
Oral	DO NOT INDUCE VOMITING. Get immediate medical attention.
Additional Information	Note to physician: Treat symptomatically.

5	Fire Fighting Measures
----------	-------------------------------

Flash Point	195 °C, 383 °F PMCC (Typical)
Extinguishing Media	CO ₂ , dry chemical, or foam. Water can be used to cool and protect exposed material.
Firefighting Procedures	Recommend wearing self-contained breathing apparatus. Water may cause splattering.
Unusual Fire & Explosion Hazards	Elevated temperatures can lead to the formation of irritating fumes and vapors. See section 10 for additional information.

6	Accidental Release Measures
----------	------------------------------------

Spill Procedures	Personal Protective Equipment must be worn, see Personal Protection Section for PPE recommendations. Ventilate area if spilled in confined space or other poorly ventilated areas. Prevent entry into sewers and waterways. Pick up free liquid for recycle and/or disposal. Residual liquid can be absorbed on inert material.
-------------------------	---

7	Handling and Storage
----------	-----------------------------

Pumping Temperature	70 °C, 158 °F
Maximum Handling Temperature	70 °C, 158 °F
Handling Procedures	Keep containers closed when not in use. Avoid breathing vapor. Avoid contact with eyes, skin and clothing. Wash

BREAK IN OIL, BR30 12 X 1QT\CS

thoroughly after handling. Launder contaminated clothing before reuse. Empty container contains product residue which may exhibit hazards of product. Dispose of packaging or containers in accordance with local, regional, national and international regulations.

Maximum Storage Temperature	Not determined.
Storage Procedures	Odorous and toxic fumes may form from the decomposition of this product if stored at temperatures in excess of 113 deg F (45 deg C) for extended periods of time or if heat sources in excess of 250 deg F (121 deg C) are used. See section 10 for incompatible materials.
Loading Temperature	Not determined.

8	Exposure Controls/Personal Protection
----------	--

Exposure Limits	None established
Other Exposure Limits	Contains mineral oil. Under conditions which may generate mists, observe the OSHA PEL of 5 mg per cubic meter, ACGIH STEL of 10 mg per cubic meter.
Engineering Controls	Material should be handled in enclosed vessels and equipment, in which case general (mechanical) room ventilation should be sufficient. Local exhaust ventilation should be used at points where dust, mist, vapors or gases can escape into the room air.
Gloves Procedures	Nitrile.
Eye Protection	Safety Glasses.
Respiratory Protection	Use half mask respirator with an organic vapor cartridge if exposure limit is exceeded. Use self-contained breathing apparatus for entry into confined space, for other poorly ventilated areas and for large spill clean-up sites.
Clothing Recommendation	Long sleeve shirt is recommended. Launder contaminated clothing before reuse.

9	Physical and Chemical Properties
----------	---

Flash Point	195 °C, 383 °F PMCC (Typical)
Upper Flammable Limit	Not determined.
Lower Flammable Limit	Not determined.
Autoignition Point	Not determined.
Explosion Data	Material does not have explosive properties.
Vapor Pressure	Not determined.
pH	Not determined.
Specific Gravity	0.87 (15.6 °C)
Bulk Density	Not determined.
Water Solubility	Insoluble.
Percent Solid	Not determined.
Percent Volatile	Not determined.
Volatile Organic Compound	Not determined.
Vapor Density	Not determined.
Evaporation Rate	Not determined.
Odor	Mild
Appearance	Amber liquid.
Viscosity	57 Centistokes (40 °C) 10 Centistokes (100 °C)
Odor Threshold	Not determined.
Boiling Point	Not determined.
Pour Point Temperature	-33 °C, -27 °F
Melting / Freezing Point	Not determined.

The above data are typical values and do not constitute a specification. Vapor pressure data are calculated unless otherwise noted.

10	Stability and Reactivity
-----------	---------------------------------

Stability	Material is normally stable at room temperature and pressure. See the Handling and Storage Section for further details.
Decomposition Temperature	Not determined.
Incompatibility	Oxidizing agents.
Polymerization	Will not occur.
Thermal Decomposition	Smoke, carbon monoxide, carbon dioxide, aldehydes and other products of incomplete combustion. Hydrogen sulfide and alkyl mercaptans and sulfides may also be released. Hydrogen sulfide may also be released.
Conditions to Avoid	High temperatures.

11	Toxicological Information
-----------	----------------------------------

BREAK IN OIL, BR30 12 X 1QT\CS

Eye Irritation	Not expected to cause eye irritation. Based on data from components or similar materials.
Skin Irritation	Not expected to be a primary skin irritant. Based on data from components or similar materials. Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying, and cracking of the skin.
Respiratory Irritation	If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract. Based on data from components or similar materials.
Dermal Toxicity	The LD50 in rabbits is > 2000 mg/Kg. Based on data from components or similar materials.
Inhalation Toxicity	No data available to indicate product or components may be a toxic inhalation hazard.
Oral Toxicity	The LD50 in rats is > 10,000 mg/Kg. Based on data from components or similar materials.
Dermal Sensitization	No data available to indicate product or components may be a skin sensitizer.
Inhalation Sensitization	No data available to indicate product or components may be respiratory sensitizers.

-- CHRONIC EXPOSURE --

Chronic Toxicity	No data available to indicate product or components present at greater than 1% are chronic health hazards.
Carcinogenicity	This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP 346 test.
Mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Reproductive Toxicity	No data available to indicate either product or components present at greater than 0.1% that may cause reproductive toxicity.
Teratogenicity	No data available to indicate product or any components contained at greater than 0.1% may cause birth defects.

-- ADDITIONAL INFORMATION --

Other	No other health hazards known.
--------------	--------------------------------

12	Ecological Information
-----------	-------------------------------

-- ENVIRONMENTAL TOXICITY --

Freshwater Fish Toxicity	Not determined.
Freshwater Invertebrates Toxicity	Not determined.
Algal Inhibition	Not determined.
Saltwater Fish Toxicity	Not determined.
Saltwater Invertebrates Toxicity	Not determined.
Bacteria Toxicity	Not determined.
Miscellaneous Toxicity	Not determined.

-- ENVIRONMENTAL FATE --

Biodegradation	Adequate data is not available to estimate the biodegradation potential of this material.
Bioaccumulation	Less than 1.0% of the components potentially bioconcentrate, based on octanol/water coefficients.
Soil Mobility	Not determined.

13	Disposal Considerations
-----------	--------------------------------

Waste Disposal	This material, if discarded, is not a hazardous waste under RCRA Regulation 40 CFR 261. Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.
-----------------------	--

14	Transport Information
-----------	------------------------------

ICAO/IATA I	Not regulated.
ICAO/IATA II	Not regulated.
IMDG	Not regulated.
IMDG EMS Fire	Not applicable.
IMDG EMS Spill	Not applicable.
IMDG MFAG	Not applicable.
MARPOL Annex II	Not determined.
USCG Compatibility	Not determined.
U.S. DOT Bulk	Not regulated.
DOT NAERG	Not applicable.
U.S. DOT (Intermediate)	Not regulated.
U.S. DOT Intermediate NAERG	Not applicable.
U.S. DOT Non-Bulk	Not regulated.
U.S. DOT Non-Bulk NAERG	Not applicable.
Canada	Not regulated.
Mexico	Not regulated.
Bulk Quantity	85000 KG, 187391 lbs.

BREAK IN OIL, BR30 12 X 1QT\CS

Intermediate Quantity 11000 KG, 24251 lbs.
Non-Bulk Quantity 400 KG, 882 lbs.

Review classification requirements before shipping materials at elevated temperatures.

15	Regulatory Information
-----------	-------------------------------

-- Global Chemical Inventories --

USA All components of this material are on the US TSCA Inventory or are exempt.

Other TSCA Reg. None known.

EU All components are in compliance with the EC Seventh amendment Directive 92 /32/EEC.

Japan All components are in compliance with the Chemical Substances Control Law of Japan.

Australia All components are in compliance with chemical notification requirements in Australia.

New Zealand All components are in compliance with chemical notification requirements in New Zealand.

Canada All components are in compliance with the Canadian Environmental Protection Act and are present on the Domestic Substances List.

Switzerland All components are in compliance with the Environmentally Hazardous Substances Ordinance in Switzerland.

Korea All components are in compliance in Korea.

Philippines All components are in compliance with the Philippines Toxic Substances and Hazardous and Nuclear Wastes Control Act of 1990 (R.A. 6969).

China All components of this product are listed on the Inventory of Existing Chemical Substances in China.

-- Other U.S. Federal Regulations --

SARA Ext. Haz. Subst. This product does not contain greater than 1.0% of any chemical substance on the SARA Extremely Hazardous Substances list.

SARA Section 313 From 1 to 4.9 percent zinc compounds; contains 0.3% as Zn.

SARA 311 Classifications

Acute Hazard	No
Chronic Hazard	No
Fire Hazard	No
Reactivity Hazard	No

CERCLA Hazardous Substances None known.

-- State Regulations --

Cal. Prop. 65 This product contains the following chemical(s) known to the state of California to cause cancer and/or birth defects based on maximum impurity levels of components: < 0.05 ppm arsenic < 0.05 ppm cadmium < 0.1 ppm lead

-- Product Registrations --

U.S. Fuel Registration Not applicable.

Finnish Registration Number Not Registered

Swedish Registration Number Not Registered

Norwegian Registration Number Not Registered

Danish Registration Number Not Registered

Swiss Registration Number Not Registered

Italian Registration Number Not Registered

-- Other / International --

Miscellaneous Regulatory Information Not determined.

16	Other Information
-----------	--------------------------

US NFPA Codes

Health	Fire	Reactivity	Special
1	1	0	N/E

(N/E) - None established

HMIS Codes

Health	Fire	Reactivity
0	1	0

Precautionary Labels

- This material has no known health hazards.

Revision Indicators

This MSDS has no revisions since 2 December 2010

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local regulations remains the

BREAK IN OIL, BR30 12 X 1QT\CS
responsibility of the user.